QUIET HOUSE DESIGN PACKAGES FOR RESIDENCE ADJACENT TO MARMION AVENUE OR MITCHELL FREEWAY

AREA TYPE	ORIENTATION	PACKAGE A	PACKAGE B
Bedrooms	Facing Road	Casement or awning windows with 6.38mm laminated glass Eaves enclosed with 6mm compressed fibre cement board Hinged doors only, fitted with acoustic seals No vents to outside walls/eaves	Casement or awning windows with 10.38mm or 6.5mm laminated glass Eaves enclosed with 6mm compressed fibre cement board No external doors No vents to outside walls/eaves
	Side-on to Road	Casement or awning windows with 6.38mm laminated glass Eaves enclosed with 6mm compressed fibre cement board No vents to outside walls/eaves	Casement or awning windows with 6.38mm laminated glass Eaves enclosed with 6mm compressed fibre cement board No vents to outside walls/eaves
	Away from Road	No Requirements	No Requirements
Living and Work Areas	Facing Road	Casement or awning windows with 6.38mm laminated glass Eaves enclosed with 6mm compressed fibre cement board 35mm (min) solid core external doors with acoustic seals Sliding doors to be fitted with acoustic seals and have overlapping meeting stiles No vents to outside walls/eaves	Casement or awning windows with 10.38mm or 6.5mm laminated glass Eaves enclosed with 6mm compressed fibre cement board No vents to outside walls/eaves Sliding doors to be fitted with acoustic seals and have overlapping meeting stiles Front door to be 40mm solid core with acoustic seals
	Side-on to Road Away from Road	Casement or awning windows with 6mm glass Eaves enclosed with 6mm compressed fibre cement board	Casement or awning windows with 6.38mm laminated glass Eaves enclosed with 6mm compressed fibre cement board
Other indoor areas	Away from Road Any orientation	No Requirements	No Requirements No Requirements
Other indoor areas	Any onentation	No Requirement	No requirements

Note: Package B+ is as for Package B but with reduced window areas (Maximum of 2m²) for bedroom windows facing Marmion Avenue.

QUIET HOUSE DESIGN REQUIREMENTS FOR RESIDENCE ADJACENT TO PASSENGER RAILWAY LINE

AREA TYPE	ORIENTATION	MODIFIED PACKAGE A
Bedrooms	Facing Railway Line	Casement or awning windows with 6.38mm laminated glass Eaves enclosed with 6mm compressed fibre cement board No vents to outside walls/eaves
	Side-on to Railway Line	Casement or awning windows with standard glass Eaves enclosed with 6mm compressed fibre cement board
	Away from Railway Line	No Requirements
Living and Work Areas	Facing Railway Line	Casement or awning windows with 6mm glass Eaves enclosed with 6mm compressed fibre cement board No vents to outside walls/eaves
	Side-on to Railway Line	Eaves enclosed with 6mm compressed fibre cement board
	Away from Railway Line	No Requirements
Other indoor areas	Any orientation	No Requirements