


ORDERED, OR MANUFACTURED UNTIL

CONTRACT, ADDENDA, ENERGY REPORT, PRECEDENCE OVER WORKING DRAWINGS.

ALL WINDOWS TO COMPLY WITH BCA 3.9.2.5 "PROTECTION OF OPENABLE WINDOWS"


FURTHER DETAILS, INCLUDING SUBFLOOR,




2.

GROUND FLOOR

Drawn:		Date:		Rev:	Page:
A.Mayes		9/05/20		-	
Scale:	Size:		Job No:	B	03
1 = 100	A3		N/A		
				-	





GENERAL NOTES:

NO WORK IS TO BE COMMENCED, ORDERED, OR MANUFACTURED UNTIL ALL RELEVANT APPROVALS AND PERMITS HAVE BEEN RECEIVED. 2.

ALL CONSTRUCTION TO COMPLY WITH ALL RELEVANT AUSTRALIAN STANDARDS AND NCC / BCA REQUIREMENTS.

CONTRACT, ADDENDA, ENERGY REPORT, AND ENGINEERING PLANS TAKE PRECEDENCE OVER WORKING DRAWINGS.

CHECK ALL DIMENSIONS ON SITE PRIOR TO CONSTRUCTION.

INSULATION TO COMPLY WITH REQUIREMENTS AS NOTED IN THE ENERGY ASSESSMENT REPORT.

TERMITE TREATMENT TO COMPLY WITH BCA 3.1.3 AND A.S. 3660-2014.

ALL WINDOWS TO COMPLY WITH BCA 3.9.2.5 "PROTECTION OF OPENABLE WINDOWS"

REFER TO ENGINEERING PLANS FOR FURTHER DETAILS, INCLUDING SUBFLOOR, ROOF, AND STAIR DETAILS.

90mm TIMBER FRAMED INTERNAL AND EXTERNALL WALLS UNLESS NOTED OTHERWISE

FINAL POSITION OF CEILING EXHAUST FANS DETERMINED ON SITE TO SUIT ROOF FRAME MEMBERS.

CEILING MANHOLES TO BE 550x500 (NOGGED OUT).

LIFT-OFF HINGES TO ALL INTERNAL OPENING WC DOORS.

DP LOCATIONS ARE DIAGRAMMATIC ONLY AND MAY BE MOVED AT ROOF PLUMBER'S DISCRETION.

ALL SOLID OR GLAZED DOORS TO HAVE 3 HINGES.



N-JONES No.7) LACE CKS WA 6037

