

20-272.1

13 October 2021

Ms Alicia Jones
Fabcot Pty Ltd
135 Kewdale Road
KEWDALE WA 6105

Dear Alicia

Woolworths Two Rocks – Services Assessment

Pritchard Francis has been engaged to prepare this services report for Alicia Jones of Woolworths Group. The purpose of this report is to identify existing site conditions, existing services, and potential upgrades required in order to facilitate the Woolworths development on the corner of Lisford Ave and Azzurra St, Two Rocks.

The development area is located within the City of Wanneroo and is bordered by Lisford Ave to the east, and the abandoned Atlantis Marine Park to the west. Figure 1 below depicts an aerial photograph of the area. Figure 1 below depicts an aerial photograph of the area.



Figure 1 – Aerial Photograph of Proposed Development Site (June 2020)

1 Geology

Coffey Geosciences completed a detailed geotechnical investigation on the site in 2006. The subsurface conditions are generally consistent and can be typically described as:

- Topsoil: sandy and silty, brown, only at test pits near Enterprise Ave and Charnwood Ave, 0.15-0.20m
- Sandy FILL: fine to medium grained, orange, dark grey, pale orange/brown and grey to dark grey; inter-bedded with dry, medium dense to very dense sand; 0.8-1.8m
- SAND: fine to medium grained; pale yellow/brown, grey and brown; dry to moist; medium dense to very dense; 0.15-5.9m
- LIMESTONE: fine to medium grained; pale yellow; variably cemented, 0.6-5.9m, although not encountered at the proposed Woolworths development site.

A classification of Class 'P' is judged to be appropriate for the site based on the presence of fill material across the site. In order to achieve a site classification of 'A', the site will need to be prepared in accordance with the Coffey site preparation specification:

- All organic materials and uncontrolled fill to depths varying up to 0.25m should be stripped and stockpiled.
- Black plastic lining found in several test pits in the area of the abandoned superficial lakes should be removed from the site.

- Uncontrolled fill primarily located in the western and central parts of the site should be removed within the building footprints down to the natural sandy material and replaced with engineering fill to the founding level.

Pritchard Francis anticipate that JDSI will undertake the site remediation and bulk earthworks in a manner which achieves a site classification of 'A'.

An infiltration rate of 5m/day is anticipated, and stormwater detention structures will be located in the existing in-situ sand. Soakwells should not be located within 3.0m of footings.

2 Sewerage Reticulation

The Water Corporation Esinet data indicates that the Woolworths development area is located adjacent to the following sewer reticulation mains:

- Ø450mm existing glass reinforced plastic (GRP) sewer reticulation main located in the western verge of Lisford Ave, discharging to the south.
- Ø150mm existing PVC sewer reticulation main located in the southern verge of Azzurra St. This is a short 11m main that connects into the abovementioned Ø450mm GRP sewer, ultimately discharging south.

As part of the subdivision works, the JDSI sewer reticulation plan depicts that the Ø150mm existing PVC sewer within the southern verge of the northern road reserve will be removed and replaced with a new Ø225mm PVC reticulation main. The new sewer main will provide two Ø150mm lot connections into the Woolworths development site. A third lot connection will be provided within the northern verge of the southern road reserve.

3 Water Reticulation

The Water Corporation Esinet data indicates that the Woolworths development area is located in proximity to the following water reticulation mains:

- Ø150mm AC reticulation main located in the western verge of Enterprise Ave.
- Ø150mm PVC reticulation main located in the western verge of Lisford Ave.

As part of the subdivision works, the JDSI water reticulation plan shows that the abovementioned Ø150mm PVC main will be extended further south along Lisford Ave. Subsequently, a Ø150mm PVC main will also be constructed within the southern verge of the northern road reserve and link to the existing Ø150mm PVC in Enterprise Ave. It is anticipated that a future water and fire connection from this main can be utilised to service the Woolworths development.

Ultimately, Pritchard Francis anticipate that a water reticulation main will also be provided within the southern road reserve abutting the southern boundary of the Woolworths development, and a lot connection from this alternative main could also be utilised to service the Woolworths development.

Pritchard Francis do not have access to water pressure and flow test results. A hydraulic consultant will be required to assess each the development site in order to:

- Size the potable water and fire connections to the Woolworths development site.
- Review the water pressure and flow within the existing water mains to verify whether pumps and tanks are necessary to support the proposed Woolworths development.

4 Stormwater Drainage

4.1 City of Wanneroo Drainage Infrastructure

The City of Wanneroo stormwater drainage data indicates that the Woolworths development area is located in proximity to the following stormwater assets:

- Stormwater pit and pipe system located in the eastern verge of Lisford Ave. The JDSI stormwater drainage layout plan also depicts this data with additional invert levels and pipe sizes.

As part of the subdivision works, the JDSI drainage layout plan shows that a Ø300mm stormwater pit and pipe system will be constructed in the southern verge of the northern road reserve, discharging west towards a temporary basin. Pritchard Francis understand that the temporary basin will be ultimately be replaced with a POS abutting the western boundary of the Woolworth development, adjacent to the loading dock / service yard.

Pritchard Francis anticipate that a stormwater drainage pit and pipe network will also be installed within 'Road 3' abutting the southern boundary of the Woolworths development, discharging west towards the ultimate POS.

4.2 City of Wanneroo Drainage Requirements

The City of Wanneroo requires that stormwater drainage infrastructure for private, commercial properties cater for storm events up to the 1:100 ARI / 1% AEP 24-hour event, however the UWMP which is yet to be endorsed by the City of Wanneroo nominates that the development site only needs to detain a 20% AEP of 24 hour duration.

Given that Pritchard Francis will be able to implement an overland flow path to the north western corner of the site, we will not need to design for the critical storm event.

Pritchard Francis anticipates that stormwater drainage for this site will be retained on site and infiltrated via localised soakwells or detention cells.

5 Gas Supply

A Dial Before You Dig investigation indicates that there is existing gas infrastructure within the vicinity of the proposed Woolworths development as below:

- Ø225mm PE high pressure 700 kPa rated main, located within the eastern verge of Lisford Ave.

Pritchard Francis do not have access to any proposed gas design drawings. However, as part of the subdivision works, it is anticipated that a gas service will be constructed on the same alignment as the water reticulation main within the northern and southern road reserves. As such, it is expected that the Woolworths development site will be serviced via this new gas main.

6 Electrical Supply

A Dial Before You Dig investigation indicates there is existing power infrastructure within the vicinity of the proposed Woolworths development as below:

- High Voltage main (overhead) located within the eastern verge of Lisford Ave.
- Low Voltage main (overhead) located within the eastern verge of Lisford Ave.
- Low Voltage main (underground) located within the eastern verge of Enterprise Ave.
- Low Voltage main (underground) located within the eastern verge of Lisford Ave.
- Streetlighting located within the eastern verge of Enterprise Ave.
- Streetlighting located within the eastern verge of Lisford Ave.

Additionally, the JDSI power drawings include the following proposed services:

- Streetlighting located within the eastern verge of Enterprise Ave.
- Streetlighting located within the southern verge of the northern road reserve.
- 630kVA transformer and RMU site on the eastern boundary of the site, with high voltage underground cables connecting to the existing high voltage mains in the eastern verge of Lisford Ave.

The proposed 630kVA transformer site will be located at the Lisford Ave verge level, whilst the commercial tenancies on the eastern boundary of the Woolworths development site are likely to be set 2m above the verge level. Fire protection of the tenancies within close proximity to the transformer will need to be considered.

Based on past experience with Woolworths developments, it is anticipated that a 1 MVA substation including a HV switchgear and site main switchboard (SMSB) will be required to service the proposed development.

The Western Power Network Capacity Mapping Tool indicates that the land development area is fed by the Yanchep substation. The remaining capacity on the network is between 20-25 MVA – there should be sufficient capacity to service the Woolworths development. An electrical engineering consultant will be required to confirm the remaining capacity and any other potential upgrades required to facilitate the development.

7 Communications

A Dial Before You Dig investigation indicates that there is existing communications infrastructure within the vicinity of the proposed Woolworths development as below:

- NBN pit and pipe network (Ø100 mm, P3 pits) located within the eastern verge of Lisford Ave.
- Telstra pit and pipe network (Ø50 mm, D pits) located within the eastern verge of Lisford Ave.
- Various Telstra conduits and pits located within the abandoned Atlantis Marine Park.

There is also an existing Ø50mm Telstra lead-in to the western portion of the development site. It is anticipated that these connections were previously utilised for the abandoned Atlantis Marine Park development. Advice from NBN will need to be requested to confirm the extents of the removal/relocation of these existing services and/or if these connections can be utilised to facilitate the Woolworths development.

Additionally, the JDSI communications drawings include the following proposed services:

- NBN pit and pipe network (Ø100 mm, P5 pits) located within the western verge of Enterprise Ave.
- NBN pit and pipe network (Ø100 mm, P5 pits) located within the southern verge of the northern road reserve.

Furthermore, a Ø50mm lot connection has been provided at the northeast corner of the site. It is anticipated that this connection would be utilised to facilitate the Woolworths development. Ideally, the communications lot connection would be relocated by JDSI to the far western boundary of the development site to be in close proximity to the Woolworths box.

8 Conclusion

This report outlines the geotechnical conditions, existing road reserves and services supporting the proposed Woolworths development on Lismore Ave and Azzurra St. A geotechnical investigation has been completed, and the site is founded on sand, and is therefore geotechnically suitable for development. Pritchard Francis confirm that, based on the proposed JDSI subdivision works, the site is accessible and can be serviced with water, sewer, gas, stormwater drainage, electrical and communications infrastructure, and that additional service support may be required due to the increase in demand as a result of the proposed development.

Yours sincerely

A handwritten signature in black ink, appearing to read 'J. De Palma'.

JAMIE DE PALMA
Project Director - Civil
Perth

20-272.1

1 November 2021

Ms Alicia Jones
Fabcot Pty Ltd
135 Kewdale Road
KEWDALE WA 6105

Dear Alicia

Woolworths Two Rocks – Civil Design Certification

We confirm that we have carried out the civil design for the above project for the roads and car parks in accordance with the requirements of Austroads and relevant Australian Standards.

The stormwater drainage design for the development has been undertaken in accordance with the City of Wanneroo requirements to contain a 100 ARI (1% AEP) event of 24 hour duration.

With a development area of 16,950m² including future south-eastern pad site, it is proposed that all stormwater be contained on site via 80 soakwells of Ø1800mm by 1800mm depth, which will provide an on-site detention of 366.4m³.

We confirm a Geotechnical Consultant has undertaken a site investigation and the subsurface profile will be suitable for on site detention and infiltration, with an anticipated permeability rate of 5m/day.

The civil drawings adequately convey the intent of the civil design and are numbered as follows:

| Drawing No. | Drawing Title | Rev |
|----------------|----------------|-----|
| 20272-C8-DG-03 | Civil DA Plans | B |

Please contact our office should you require further information.

Yours sincerely



JAMIE DE PALMA
Project Director - Civil
Perth

Geotechnical Data - Douglas Partners 13 August 2021

5 sets of infiltration tests undertaken returned values all in excess of 19m/day.

Utilise 5m/day for stormwater detention calculations.

Geotechnical Data - Coffey 24 May 2006

Typical subsurface profile

- Topsoil varies from 0.15-0.20m
- Sandy Fill varies from 0.8m - 1.8m
- Sand varies from 0.15m to 5.9m
- Limestone varies from 0.6m to 5.9m

Bulk Earthworks

Typically will require several metres of clean fill to achieve the desired pad level, therefore existing limestone will not impact the performance of the stormwater network.

Stormwater Calculations in accordance with anticipated geotechnical conditions

Stormwater Event: City of Wanneroo 100 ARI (1% AEP) of 24 Hour Duration

Development Impervious Area incl future pad site = 16,950 m²
 Equivalent Impervious Area (@ 0.95) = 16,102 m²
 Assumed permeability rate = 5m/day


Volume of a dia 1800mm x 1800mm deep soakwell = 4.58m³

Infiltration of a dia 1800mm x 1800mm deep soakwell
 = r² + 2 rh @ 25%
 = x0.9x0.9 + 2 x0.9x1.8x0.25
 = 5.09m² of permeability area

Infiltration achieved for one soakwell
 = 5.09m² @ 5m/day
 = 25.45m³/day of infiltration
 Soakwell capacity over 24 hours = volume + infiltration = 30.03m³ per day

Stormwater Volume
 = CIA/3600
 = 0.95 x 6.17 x 16,950 / 3600
 = 27.59 L/s
 = 2,384.4 m³ over 24 hours

2,384.4 m³ / 30.03m³ = 80 (79.40) soakwells required to service the site.



DA ISSUE
ISSUED FOR DEVELOPMENT APPROVAL

| Rev. | Amendment | Date |
|------|---------------------|----------|
| A | FOR INFORMATION | 24/1/20 |
| B | FOR INFORMATION | 17/02/21 |
| C | FOR INFORMATION | 05/03/21 |
| D | FOR INFORMATION | 09/03/21 |
| E | FOR CLIENT ISSUE | 18/03/21 |
| F | FOR INFORMATION | 19/03/21 |
| G | FOR INFORMATION | 23/03/21 |
| H | FOR CLIENT REVIEW | 25/03/21 |
| J | DRP PRESENTATION | 08/07/21 |
| K | DRP PRESENTATION 2 | 20/07/21 |
| L | ISSUE FOR REVIEW | 16/08/21 |
| M | ISSUE FOR REVIEW | 01/09/21 |
| N | FOR REVIEW | 09/09/21 |
| P | FOR REVIEW | 13/09/21 |
| Q | FOR REVIEW | 14/09/21 |
| R | FOR CLIENT APPROVAL | 17/09/21 |
| S | FOR CLIENT APPROVAL | 06/10/21 |
| T | DA ISSUE | 15/10/21 |

WOOLWORTHS SITE

| | |
|----------------------------------------------------|---------------------|
| TOTAL SITE AREA | 16929m ² |
| SITE AREA | 15227m ² |
| WOOLWORTHS (WITH EXPANSION) | 3600m ² |
| WOOLWORTHS (WITHOUT EXPANSION) | 2942m ² |
| FUTURE EXPANSION - INCL OFFICE MEZZANINE | 658m ² |
| CAFE | 85m ² |
| SPECIALTY 1 (LIQUOR) | 200m ² |
| SPECIALTY 2 | 82m ² |
| SPECIALTY 3 | 78m ² |
| SPECIALTY 4 | 151m ² |
| RETAIL / COMMERCIAL | 595 m ² |
| TOTAL AREA | 4791m ² |
| PARKING REQUIRED WW - 5 BAYS/100m ² GLA | 240 BAYS |

FUTURE PAD SITE

| | |
|-----------|---------------------|
| SITE AREA | 1702 m ² |
|-----------|---------------------|

PARKING PROVIDED

| | |
|----------------|----------|
| GENERAL | 226 BAYS |
| STREET PARKING | 10 BAYS |
| PICKUP | 6 BAYS |
| TOTAL | 242 BAYS |



DISCLAIMER: The drawing(s) provided hereunder shall be used for the purposes for which it was provided. The electronic data files for all or part of the drawings carry no guarantee whatsoever as to their accuracy, content or lack of same. The use of electronic data files are at the requesters or any other third party user's risk. They cannot be used for any contractual purposes. The user of these files must verify the electronic data files against the hard copy or pdf file provided.

BROWN FALCONER


9/300 Rokeby Road, Subiaco, Western Australia 6004
 Telephone : 08 6382 0303 ABN 65 007 846 586
 brownfalconer.com.au

FABCOT PTY LTD

WOOLWORTHS TWO ROCKS


SITE PLAN

Scale As indicated
 Drawn DF Checked MJ
 Date 15/10/21
 Job No. 2020050
 Dwg No. 3353 02 Rev: T A1 SHEET




TYPICAL SEMI-MOUNTABLE KERB DETAIL

SCALE 1:10
NOTE: ALL RADII ARE 20mm U.S.O.




TYPICAL BARRIER KERB DETAIL

SCALE 1:10



TYPICAL FLUSH KERB DETAIL


SCALE 1:10
NOTE: ALL RADII ARE 10mm U.S.O.



TYPICAL CARPARK PAVEMENT DETAIL


SCALE 1:10

NOTE:
THE CONTRACTOR SHALL CONSTRUCT PAVEMENT IN ACCORDANCE WITH AS2150 AND CIVIL SPECIFICATIONS AND DETAILS




TYPICAL SEMI-MOUNTABLE KERB CONCRETE PINNING DETAIL

SCALE 1:10
NOTE: ALL RADII ARE 20mm U.S.O.




TYPICAL BARRIER KERB CONCRETE PINNING DETAIL

SCALE 1:10
NOTE: ALL RADII ARE 50mm U.S.O.



ELEVATION


SCALE 1:20



PLAN VIEW

TYPICAL RECYCLED WHEEL STOP DETAIL

SCALE 1:100




SECTION

SCALE 1:10


DETAIL

SCALE 1:2



KERB EXPANSION JOINT AND CRACK CONTROL DETAILS

SCALE 1:200



TYPICAL SAW CUT DETAIL

SCALE 1:20


ACCESIBLE PARKING SPACE NOTES

SPACE IDENTIFICATION
EACH DEDICATED SPACE SHALL BE IDENTIFIED BY MEANS OF A WHITE SYMBOL OF ACCESS IN ACCORDANCE WITH AS1428:1 BETWEEN 800mm AND 1000mm HIGH PLACED ON A BLUE RECTANGLE WITH NO SIDE MORE THAN 1200mm, PLACED AS A PAVEMENT MARKING IN THE CENTRE OF THE SPACE BETWEEN 500mm AND 600mm FROM ITS ENTRY POINT AS ILLUSTRATED.

SPACE DELINEATION
PAVEMENT MARKINGS SPECIFIED IN ITEMS (A) AND (B) OF THIS CLAUSE SHALL BE YELLOW AND SHALL HAVE A SLIP RESISTANT SURFACE. RAISED PAVEMENT MARKERS SHALL NOT BE USED FOR SPACE DELINEATION.

PAVEMENT MARKINGS SHALL BE PROVIDED AS FOLLOWS:


- LINEMARKING:**
 - DEDICATED PARKING SPACES SHALL BE OUTLINED WITH UNBROKEN LINES 80 TO 100mm WIDE ON ALL SIDES EXCEPTING ANY SIDE DELINEATED BY A KERB, BARRIER OR WALL.
 - SHARED AREAS SHALL BE MARKED AS FOLLOWS:
 - WALKWAYS WITHIN OR PARTLY WITHIN A SHARED AREA SHALL BE MARKED WITH UNBROKEN LONGITUDINAL LINES ON BOTH SIDES OF THE WALKWAY EXCEPTING ANY SIDE DELINEATED BY A KERB, BARRIER OR WALL.
 - OTHER VACANT NON-TRAFFICKED AREAS, WHICH MAY BE INTENTIONALLY OR UNINTENTIONALLY OBSTRUCTED (E.G. BY UNINTENDED PARKING), SHALL BE OUTLINED WITH UNBROKEN LINES 80mm TO 100mm WIDE ON ALL SIDES EXCEPTING ANY SIDE DELINEATED BY A KERB, BARRIER OR WALL, AND MARKED WITH DIAGONAL STRIPES 150mm WIDE WITH SPACES 300mm BETWEEN STRIPES. THE STRIPES SHALL BE AT AN ANGLE OF 45° TO THE SIDE OF THE SPACE.
 - NO SHARED AREA MARKINGS SHALL BE PLACED IN TRAFFICKED AREAS.
 - ALL LINEMARKING MUST BE NON SLIP.
- BOLLARDS:**
 - MINIMUM HEIGHT 1300mm.
 - RECOMMENDED COLOUR BLUE TO CONTRAST AGAINST YELLOW LINE MARKING.




PERPENDICULAR ACCESSIBLE CAR PARKING SPACES IN ACCORDANCE WITH AS2890.6

SCALE 1:50







CONCRETE PATH SECTION
SCALE 1:25 0m 0.5m 1.0m




EXPANSION JOINT
SCALE 1:10 0m 200mm 400mm




CONTRACTION JOINT
SCALE 1:10 0m 200mm 400mm




TYPICAL CONCRETE PATH PLAN
SCALE 1:100 0m 2m 4m




DETAIL
SCALE 1:2 0m 20mm 40mm



SECTION A
SCALE 1:25 0m 250mm 500mm




FRONT ELEVATION
SCALE 1:25 0m 0.5m 1.0m



TYPICAL KERB RAMP DETAIL
SCALE 1:50 0m 1m 2m

- NOTES**
1. ALL CONCRETE TO BE A MINIMUM OF 25MPa, 20mm AGGREGATE AND A MAXIMUM SLUMP OF 80mm, FROM AN APPROVED PRE-MIX BATCH PLANT
 2. MINIMUM THICKNESS - 100mm.
 3. BEDDING - SAND, 50mm MINIMUM.
 4. FINISH - BROOMED TO NON-SKID FINISH PARALLEL TO LINE OF KERB WITH TOOLED EDGES
 5. EXPANSION JOINTS - APPROVED MATERIAL SHALL BE EXPANDITE-FLEXICELL.
 6. TACTILE GROUND SURFACE INDICATORS (T.G.S.I.'s) SHALL BE IN ACCORDANCE WITH AS1428.1 AND AS1428.4.
 7. CONTRACTOR TO INSTALL 2x ROWS OF TERRACOTTA WARNING T.G.S.I.'s (ADHESIVE TYPE) FOR FULL WIDTH OF CONCRETE KERB RAMP.
 8. WARNING TGSIs ARE NOT TO BE CUT. CONTRACTOR SHALL SELECT SUITABLE SIZE TO EXTEND ACROSS FULL WIDTH OF KERB RAMP (EXCLUDING SPLAYS).
 9. WHERE THE KERB RAMP IS CONSTRUCTED USING BLOCK PAVERS, THE CONTRACTOR SHALL INSTALL TGSi PAVERS IN A CONTRASTING COLOUR CONFORMING WITH AS1428.4 LUMINANCE REQUIREMENTS.






TYPICAL HEAVY DUTY BOLLARD DETAIL

SCALE 1:20 0m 400mm 800mm

NOTES

1. THE BOLLARD SHALL COMPLY WITH AS3845.
2. BOLLARD DESIGNED FOR 30kN LIGHT VEHICLE IMPACT BARRIER IN ACCORDANCE WITH AS1170.1 BARRIER LOADS.
3. REFER TO THE ARCHITECT'S DOCUMENTATION FOR LOCATIONS AND HEIGHTS.




TYPICAL BOLLARD IN ASPHALT PAVEMENT DETAIL

SCALE 1:20 0m 400mm 800mm


NOTES

1. THE BOLLARD SHALL COMPLY WITH AS3845.
2. BOLLARD DESIGNED FOR 10kN INCIDENTAL LOAD ONLY. NOT DESIGNED TO AS1170.1 BARRIER LOADS.
3. REFER TO THE ARCHITECT'S DOCUMENTATION FOR LOCATIONS AND HEIGHTS.



**FOOTING DETAIL
GENERAL / VERGE**

**FOOTING DETAIL
TRAFFIC ISLAND, PATH OR OTHER PAVED / SURFACED AREA**



TYPICAL BOLLARD IN CONCRETE PAVEMENT DETAIL


SCALE 1:20 0m 400mm 800mm

NOTES

1. THE BOLLARD SHALL COMPLY WITH AS3845.
2. BOLLARD DESIGNED FOR 10kN INCIDENTAL LOAD ONLY. NOT DESIGNED TO AS1170.1 BARRIER LOADS.
3. REFER TO THE ARCHITECT'S DOCUMENTATION FOR LOCATIONS AND HEIGHTS.

| SIGN PANEL LATERAL CLEARANCE | |
|------------------------------|---------------------|
| KERB TYPE | MIN. CLEARANCE (mm) |
| BARRIER KERB | 300 |
| SEMI-MOUNTABLE KERB | 500 |
| MOUNTABLE KERB | 500 |
| UNKERBED | 2000 |

| SIGN PANEL VERTICAL CLEARANCE | |
|---------------------------------------------|---------------------|
| DESIGN SCENARIO | MIN. CLEARANCE (mm) |
| LOCATED IN UNPAVED VERGE | |
| - FROM VERGE LEVEL | 2000 |
| - FROM PAVEMENT LEVEL | 2200 |
| WHEN OVER HANGING OR LOCATED WITHIN FOOTWAY | 2500 |



TYPICAL ROAD SIGN CLEARANCE AND FOOTING DETAILS

SCALE 1:10 0m 200mm 400mm


NOTES

1. LOCAL AUTHORITY OR CLIENT SPECIFICATIONS AND DETAILS TAKE PRECEDENCE.
2. DETAIL FOR USE IN WIND REGIONS 'A' AND 'B' ONLY. FOOTINGS FOR WIND REGIONS 'C' AND 'D' SHALL BE STRUCTURALLY ENGINEERED.
3. SIGN INSTALLATION SHALL COMPLY WITH AS2890 SERIES AND AS1742 SERIES
4. IF LOCATED WITHIN ROAD RESERVE, SIGN INSTALLATION SHALL COMPLY WITH MAIN ROADS W.A. SPECIFICATIONS AND DETAILS.




The Essential First Step.







TYPICAL BURIED LID DETAIL
SCALE 1:20




TYPICAL GULLY GRATE ON KERB LID DETAIL WITH ASPHALT PAVEMENT
SCALE 1:20




TYPICAL INVERTED GULLY GRATE LID DETAIL WITH ASPHALT PAVEMENT
SCALE 1:20



TYPICAL INVERTED GULLY GRATE LID DETAIL WITH CONCRETE PAVEMENT
SCALE 1:20



TYPICAL INTERCONNECTED SOAKWELL DETAIL
SCALE 1:20



TYPICAL SLAB CAST-IN ITEM
SCALE 1:20

STORMWATER PIT NOTES


1. ALL INSITU CONCRETE SHALL BE CLASS N32 IN ACCORDANCE WITH A1379.
2. ALL INSITU CONCRETE CORNERS SHALL HAVE A 20mm CHAMFER UNLESS OTHERWISE NOTED.
3. CEMENT MORTAR SHALL CONSIST OF ONE PART CEMENT AND THREE PARTS SAND.
4. SL81 REINFORCEMENT SHALL CONFORM WITH HARD DRAWN FABRIC TO AS4671.
5. MINIMUM CLEAR COVER TO REINFORCEMENT SHALL BE 50mm.
6. THE LINER SHALL BE REINFORCED CONCRETE MANUFACTURED TO AS4058.
7. THE MAXIMUM INLET/OUTLET PIPE OUTSIDE DIAMETER SHALL BE LESS THAN 60% OF THE LINER INTERNAL DIAMETER.
8. MINIMUM OF 40% OF LINER SHALL REMAIN IN ANY HORIZONTAL PLANE.
9. MINIMUM INTERNAL LINER SPACE OF 200mm BETWEEN PUNCHED/CUT HOLES.
10. HOLES TO BE CUT/PUNCHED ON ACCORDANCE WITH MANUFACTURER'S SPECIFICATION.
11. THE LINER SHALL HAVE EQUIVALENT PROPERTIES AND REINFORCEMENT OF CLASS 2 R.C.P. EXCEPT THAT THE REINFORCEMENT SHALL BE CIRCULAR.
12. COVERS SHALL BE CLASS 'D' TO AS3996.

| TABLE B DRAINAGE PIT BASE SOAKAGE HOLE SIZE | |
|------------------------------------------------|---------------------------|
| LINER SIZE MIN. (mm) | SOAKHOLE DIAMETER (mm) |
| 1050 | 600 |
| 1200 | 600 |
| 1500 | 900 |
| 1800 | 1200 |



The Essential First Step.





DRY CONDITIONS

WET CONDITIONS

**TYPICAL CONCRETE PIPE TRENCH DETAILS
(SUPPORT TYPE "U")**

SCALE 1:20 0m 400mm 800mm


TRENCH DETAIL NOTES

1. ALL PIPE TRENCHES SHALL BE CONSTRUCTED IN ACCORDANCE WITH AS3725 - DESIGN FOR INSTALLATION OF BURIED CONCRETE PIPES. SHOULD DISCREPANCIES EXIST, AS3725 TAKES PRECEDENCE.
2. DRY CONDITIONS SHALL BE SAND SOIL WHERE THE MAXIMUM PREDICTED GROUND WATER LEVEL (G.W.L.) IS A MINIMUM 300mm BELOW PIPE INVERT.
3. WET CONDITIONS SHALL BE CONSIDERED AS BEING IN ROCK, CLAY OR SAND WHERE THE MAXIMUM PREDICTED G.W.L. IS HIGHER THAN 300mm BELOW PIPE INVERT.
4. BEDDING CONDITION SHALL BE CARRIED PAST ALL MANHOLES, GULLIES & OTHER DRAINAGE STRUCTURES DOWNSTREAM.
5. WHERE PIPES HAVE PROTRUDING SOCKETS, SUITABLE RECESSES SHALL BE PROVIDED IN THE SUPPORTING MATERIALS TO ENSURE THAT THE PIPES DO NOT BEAR ON THE SOCKETS (TYP.)

| MINIMUM BED ZONE DEPTHS | |
|-------------------------|------------|
| SUPPORT TYPE | DEPTH (mm) |
| U | 75 |
| H / HS ≤ Ø1500 | 100 |
| H / HS > Ø1500 | 150 |

| MINIMUM SIDE CLEARANCE "L _c " (D/6 or L _c , WHICHEVER IS GREATER) | |
|--------------------------------------------------------------------------------------------|----------------|
| PIPE DIAMETER | L _c |
| ≤600 | 150 |
| >600 - ≤1200 | 200 |
| >1200 | D/6 |

NOTE:
THE MINIMUM L_c VALUES SHALL ONLY BE USED WHERE NECESSARY COMPACTION VALUES CAN BE ASSURED.



TYPICAL TRENCH GRATE


SCALE 1:10 0m 200mm 400mm

TRENCH DETAIL NOTES

1. ALL PIPE TRENCHES SHALL BE CONSTRUCTED IN ACCORDANCE WITH AS3725 - DESIGN FOR INSTALLATION OF BURIED CONCRETE PIPES. SHOULD DISCREPANCIES EXIST, AS3725 TAKES PRECEDENCE.
2. DRY CONDITIONS SHALL BE SAND SOIL WHERE THE MAXIMUM PREDICTED GROUND WATER LEVEL (G.W.L.) IS A MINIMUM 300mm BELOW PIPE INVERT.
3. WET CONDITIONS SHALL BE CONSIDERED AS BEING IN ROCK, CLAY OR SAND WHERE THE MAXIMUM PREDICTED G.W.L. IS HIGHER THAN 300mm BELOW PIPE INVERT.
4. BEDDING CONDITION SHALL BE CARRIED PAST ALL MANHOLES, GULLIES & OTHER DRAINAGE STRUCTURES DOWNSTREAM.
5. WHERE PIPES HAVE PROTRUDING SOCKETS, SUITABLE RECESSES SHALL BE PROVIDED IN THE SUPPORTING MATERIALS TO ENSURE THAT THE PIPES DO NOT BEAR ON THE SOCKETS (TYP.)




The Essential First Step.




TYPICAL LIMESTONE RETAINING WALL DETAIL - TYPE 3 - CLASS "A"

SCALE 1:25 0m 0.5m 1.0m



TYPICAL LIMESTONE RETAINING WALL "TYPE 3" ELEVATION

SCALE 1:25 0m 0.5m 1.0m



TYPICAL LIMESTONE RETAINING WALL HEADER LAYOUT


SCALE 1:25 0m 0.5m 1.0m

LIMESTONE RETAINING WALL AND FENCE NOTES

1. COMPACT GROUND UNDER FOOTING TO RESIST 8 BLOWS PER 300mm OF A STANDARD 16mm DIA PENETROMETER OVER A DEPTH OF 600mm
2. LIMESTONE BLOCKS TO BE A MINIMUM DENSITY OF 1500kg/m³ (DRY). RECONSTITUTED LIMESTONE BLOCKS TO BE A MINIMUM DENSITY OF 1800kg/m³ (DRY).
3. MORTAR MIX SHALL COMPRISE 1 PART WHITE CEMENT, 1 PART LIME PUTTY, AND 6 PARTS CLEAN YELLOW SAND OR 1 PART WHITE CEMENT, 0.5 PART LIME PUTTY AND 4.5 PARTS YELLOW SAND IF LESS THAN 1km FROM THE COAST. ALL BLOCK WORK SHALL BE FULLY MORTARED TO ADJACENT BLOCKS.
4. THESE WALLS ARE APPLICABLE FOR CLASS 'A' CONDITIONS ONLY TO AS 2870. ALL OTHER CONDITIONS TO BE REFERRED TO ENGINEER.
5. ALL RETAINING WALLS HAVE BEEN CALCULATED WITH A HORIZONTAL BACKFILL. ANY OTHER CIRCUMSTANCES TO BE ASSESSED INDIVIDUALLY.
6. THE RETAINING WALL HAS BEEN DESIGNED TO SUPPORT A 5kPa SURCHARGE.
7. INTERLOCKING BLOCK COURSING TO BE STAGGERED AS PER TYPICAL DETAIL.
8. WALL TO HAVE INTERLOCKING BLOCKS COMMENCING AT 4th COURSE FROM TOP, PERPENDICULAR TO FACING AT MAXIMUM 4m SPACING TO ACHIEVE INTERLOCK OF STRUCTURE.
9. WALLS SHALL HAVE VERTICAL CONTROL JOINTS AT INTERVALS OF NO MORE THAN 10 METRES FOR TYPE 1 WALLS, 15 METRES FOR TYPE 2 AND 3 WALLS, PREFERABLY LOCATED AT PROPERTY BOUNDARIES. JOINTS REQUIRED ALSO ON CORNERS AS PER ATTACHED DETAIL. JOINTS SHALL BE 20mm WIDE, BE FILLED WITH A 25mm CLOSED CELL FOAM AND SEALED WITH AN APPROVED POLYURETHANE JOINT FILLER.
10. NO BACKFILLING UNTIL 7 DAYS AFTER WALLS HAVE BEEN BUILT. COMPACT USING LIGHT EQUIPMENT TO DISTANCE BACK FROM THE FACE OF WALL EQUAL TO THE EFFECTIVE HEIGHT.
11. FENCE TO BE PROPRIETARY SYSTEM BY OTHERS - WALL DESIGNED FOR WIND REGION A ONLY.
12. FENCE POSTS SHALL BE AT 2400mm MAXIMUM CENTRES.
13. A NON SACRIFICIAL ANTI GRAFFITI COATING IS TO BE APPLIED TO WALLS FACING A ROAD, P.A.W. OR P.O.S.


WALL TYPE "3"

| COURSES | TOTAL HEIGHT | EFFECTIVE HEIGHT RANGE | BASE WIDTH | MIN. TOE DEPTH |
|---------|--------------|------------------------|------------|----------------|
| 4 | 1460 | 790 - 1110 | 1090 | 350 |
| 5 | 1830 | 1111 - 1480 | 1460 | 350 |
| 6 | 2200 | 1481 - 1850 | 1460 | 350 |
| 7 | 2570 | 1851 - 2170 | 1830 | 400 |
| 8 | 2940 | 2171 - 2540 | 2200 | 400 |
| 9 | 3310 | 2541 - 2810 | 2200 | 500 |
| 10 | 3680 | 2811 - 3180 | 2570 | 500 |
| 11 | 4050 | 3181 - 3550 | 2940 | 500 |




TYPICAL LIMESTONE RETAINING WALL DETAIL - TYPE 2 - CLASS "A"

SCALE 1:25 0m 0.5m 1.0m




TYPICAL LIMESTONE RETAINING WALL DETAIL - TYPE 1

SCALE 1:25 0m 0.5m 1.0m




PLAN VIEW OF CORNER CONTROL JOINT LOCATION

SCALE 1:25 0m 0.5m 1.0m




VERTICAL CONTROL JOINT DETAIL

SCALE 1:10 0m 200mm 400mm




SECTION


SCALE 1:25 0m 250mm 500mm



TYPICAL FENCING PANEL ELEVATION
SCALE 1:20



TYPICAL FENCING PANEL PLAN SPACING
SCALE 1:20



TYPICAL POST BACKSTAY SECTION
SCALE 1:20

GENERAL NOTES

1. ALL DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE NOTED
2. ALL FENCING SHALL BE IN ACCORDANCE WITH AS1725.1-2010
3. FOR ALL FENCE MATERIAL CLASSES AND TREATMENTS AND CONCRETE CLASS AND DENSITY REFER TO SPECIFICATION AND/OR MANUFACTURER'S SPECIFICATIONS
4. COATING REQUIREMENTS FOR FENCE TYPE 1 CONSISTS OF THE FOLLOWING:
 - 4.1. CHAIN WIRE MESH - 1800 x 50 x Ø3.15 PVC COATED
 - 4.2. STRAINER WIRE - SINGLE Ø4.0 HELICOIL PVC COATED
 - 4.3. Ø2.0 MESH TIE WIRE - PVC COATED
 - 4.4. STEEL PIPE - GALVANISED
 - 4.5. PRESSED CAP - GALVANISED
 - 4.6. CLIP TEE - GALVANISED
5. THE CONCRETE FOOTINGS SHALL BE N25 CONCRETE.
6. 50% SHADE CLOTH POROSITY.

