



LEGEND

PLEASE NOTE: REFER TO SPECIFICATION FOR DETAILS OF SURFACING, FINISHES AND FURNITURE.

- EXISTING CONTOURS (1M)
- PROPOSED CONTOURS
- SPOT LEVELS
+ FINISHED GROUND LEVEL
+ TW TOP OF EDGING
- EXISTING SPRINKLERS
- CONCRETE FOOTPATH
100mm depth 'grey' concrete generally 2100mm wide with broom finish. Refer to TS-09-03 for lock joint details.
- CONCRETE VEHICULAR CROSSOVER
150mm depth 'grey' concrete with 500mm ccs 'Charcoal' (or equal) strips either side of crossover with broom finish. Refer to TS-09-03 for lock joint details.
- HARDSTAND FOR SHELTER (OPTIONAL ITEM)
As per Shelter Manufacturers detail.
- CONCRETE FOOTPATH (OPTIONAL ITEM)
100mm depth 'grey' concrete generally 2100mm wide with broom finish. Refer to TS-09-03 for lock joint details.
- PS - PICNIC SHELTER (OPTIONAL ITEM)
4x4m shelter 'Apex' by 'Grillex' or equal.
Colour of roof to be 'surlimit' or equal and uprights and structure to be 'Basalt' or equal with in-ground foundations to manufacturers detail.
- SEAT (OPTIONAL ITEM)
DDA compliant seats, Atessa deluxe seats with armrests by 'Grillex' or equal approved. Seats to be 'Clear anodised' and base 'Basalt' or equal. To be surface mounted to manufacturers detail.

NOTES:

1. ALL EXISTING VEGETATION TO BE PROTECTED DURING WORKS.
2. IT IS THE CONTRACTORS RESPONSIBILITY TO SURVEY FOR SERVICES PRIOR TO CONSTRUCTION.
3. ALL DISTURBED EXISTING TURF FROM WORKS IS TO BE RECTIFIED BY THE CONTRACTOR PRIOR TO HANDOVER.

PLEASE NOTE: IT IS THE CONTRACTORS RESPONSIBILITY TO CAREFULLY REVIEW THE DRAWINGS AND SPECIFICATION, AND CHECK ALL QUANTITIES AND ENSURE THAT ALL ITEMS ARE INCLUDED IN THE SUBMISSION. ANY DISCREPANCIES TO BE REPORTED TO THE SUPERINTENDENT.