




STRETCHER BOND (BLOCKS) (190 x 190mm BLOCKS)




90 DEGREE HERRINGBONE (230 x 115mm STANDARD & 230 x 152mm PAVERS)




45 DEGREE HERRINGBONE (230 x 115mm STANDARD & 230 x 152mm PAVERS)



90 DEGREE HERRINGBONE (230 x 115mm INTERLOCK)




45 DEGREE HERRINGBONE (230 x 115mm INTERLOCK)



NOTE:

- 1. PAVERS MUST ALWAYS BE LAID ACROSS THE TRAFFIC FLOW.
- 2. ONLY THOSE PATTERNS SHOWN SHALL BE USED.
- 3. REFER TO WRITTEN SPECIFICATIONS FOR CONSTRUCTION GUIDELINES.



45 DEGREE DIAMOND (190 x 190mm BLOCKS)

SCALE: 200 0 2	200 400 600 800	DATUM:	GRID:
1:20 SCALE	IN MILLIMETRES	N/A	N/A
DESIGNED: DESIGN CHECKED:		APPROVED:	
C.O.W.	the first termination and	* B. McCAWLEY COORDINATOR ASSET PLAN	
DRAWN: C.O.W. CML DESIGNER	DESIGN ARCHIVE:	APPROVED: * B. CHANG MANAGER ASSET PLANNING	1/8/2022
DRAWING ARCHIVE:	STANDARDS CHECK: * J. SONG 1/8/2022 TRANSPORT & DRAMAGE ASSET PLANNER	APPROVED: * B. GEE DIRECTOR ASSETS	1/8/2022

CROSSOVERS AND VERGE

RESIDENTIAL
RESIDENTIAL BRICKPAVED CROSSOVER
APPROVED LAYING PATTERNS

OVED LAYING PATTERNS

FILE No.

N/A

PROJECT No.

N/A

CITY OF WANNEROO ASSETS

No.
N/A
TS

TS 07 -8-3



ORIGINAL DRG. SIZE

A3