

North Precinct Trinity Marmion Avenue, Alkimos

outbuildings and garages/carports shall be constructed within the nominated building envelopes as depicted on the Plan.

development of a single house.

Residential Design Codes apply unless otherwise provided for

R-Coding	R30	1
Minimum Open Space	35% (i)	1
Building Setbacks	Minimum	1
Primary Street (Piazza Link)	4.0m	1
Side	Refer Provisions Below	1
Laneway (dwelling & garages)	1.0m	1
Second storey	1.5m min. where depicted on plan	1

## GENERAL PROVISIONS

- (i) Outdoor living areas to be located on the northern or eastern
- (ii) Side Setbacks:
  - length of that boundary behind the front setback line.
  - · A second zero lot line is permitted on the other side boundary of the lot behind the front setback line, however the wall length shall not exceed 6 metres.
  - of 3.5 metres with an average of 3 metres.
- (iii) Balconies, porticos and verandahs (subject to the Building Code of Australia and engineering constraints) may project not more than one metre into the front setback area.

## **ENDORSEMENT**

This Detailed Area Plan has been endorsed by Council under Clause 9.14.3(d) of District Planning Scheme No. 2

Manager Planning Implementation - City of Wanneroo



1. Pavements and footpaths shown diagrammatically only 2. Lot numbers will change pending preparation of Deposited Plan **DETAILED AREA PLAN 35** SANTORINI NORTH PRECINCT - PHASE 4 LOT 9004 MARMION AVENUE, ALKIMOS

TRINITY ESTATE

1811

1003 GH

1002

1001

1000

POND.

1005

993

994

PRIMARY STREET SETBACK

SECOND STOREY SETBACK

ZERO LOT LINE WHERE DEPICTED

REFER TO NOTE (ii)

TO PIAZZA LINK 4.0m MINIMUM

1.5m MINIMUM

8m LANEWAY

998

15m ROAF

977

976

1004



LOCATION PLAN



# **PROVISIONS**

The provisions addressed below relate to Phase 4 - Santorini

Unless otherwise approved by the City of Wanneroo, all dwellings,

This DAP replaces the need to obtain Planning Approval for the

### R-CODES VARIATIONS

The City of Wanneroo District Planning Scheme No. 2 and below.

The following standards represent variations to the R-Codes and operate as Acceptable Development requirements.

	R-Coding	R30	
	Minimum Open Space	35% (i)	38
	Building Setbacks	Minimum	
	Primary Street (Piazza Link)	4.0m	
	Side	Refer Provisions Below	
	Laneway (dwelling & garages)	1.0m	1
	0	1 Em min where denisted on plan	1

- boundary where practicable for solar access.
  - A zero lot line is permitted on one side boundary for 2 / 3 the
  - Wall heights on zero lot lines shall have a maximum height



926 GH

1018

1019

1020

1021

1028

1022

1023

1024

1025

1026

MINOAN

1.5m MINIMUM

1027

131

SECONDARY STREET SETBACK

925 924

923 922

1035

1034

1033

多

1042

1032

1031

1030

1029

921

MERC!

1039

GARAGE SETBACK

1041

1043

1.0m MINIMUM

1040

1044